



Specifications Noxion LED Downlight Slim V2.0 12W 1200lm 120D - 830 Warm White | 170mm - Cutout 150mm - IP44

[View Product](#)

General Information

| | |
|--------------------------|--|
| SKU | 238898 |
| EAN | 8719157014878 |
| Brand | Noxion |
| Manufacturer Name | Noxion LED Downlight Slim V2.0 IP44 12W 3000K Cutout Ø150mm Frame Ø170mm |
| Any Lamp all-in warranty | 6 Years |
| Average Lifetime (h) | 50000 |

Technical Information

| | |
|-----------------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Wattage | 12 |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 830 Warm White |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |
| Driver Included | Yes |

| | |
|--------------------------|---------------------------------------|
| Beam Angle (degree) | 120 |
| Luminous Flux (Lumen) | 1200 |
| Luminous Efficacy (lm/W) | 100 |
| Power factor | >0.90 |
| Installation Depth (mm) | 19 |
| Unified Glare Rating | < 28 - for hallways and storage rooms |
| Optical Cover | PC (Polycarbonate) |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|-------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 150 |
| IP-rating | IP44 |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature | -20 to +40 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Colour of material | White |
| Series | Slim |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 26 |
| Diameter (mm) | 170 |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



Easy return process