



Specifications Multipack 4x Philips LED Downlight DN065C Metal 12W 1200lm 110D - 830 Warm White | 175mm - Cutout 150mm - IP20



[View Product](#)

General Information

| | |
|--------------------------|------------------------------------------------------|
| SKU | 257498 |
| EAN | 8719157070812 |
| Brand | Philips |
| Manufacturer Name | Multipack 4x DN065C G4 LED12/830 12W 220-240V 6-D175 |
| Any Lamp all-in warranty | 3 Years |
| Average Lifetime (h) | 30000 |

Technical Information

| | |
|-----------------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Wattage | 12 |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 830 Warm White |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |
| Including bulb | Yes |

| | |
|--------------------------|---------------------------------------|
| Amount of bulbs required | 1 |
| Beam Angle (degree) | 110 |
| Luminous Flux (Lumen) | 1200 |
| Luminous Efficacy (lm/W) | 100 |
| Power factor | >0.90 |
| Unified Glare Rating | < 28 - for hallways and storage rooms |
| Optical Cover | Plastic |
| Finish of Reflector | Frosted |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|------------------------|
| Mounting Method | Surface |
| Cut out (mm) | 150 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature | -20 to +40 |
| Housing | Metal |
| Colour of the Fixture | White |
| Fixture Connection | Screw terminal, 2-pole |
| Series | DN065C |

Dimensions

Diameter (mm)

Why Any-lamp?

175

Sensor Information  Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



Easy return process